

### Product type designation

Product description

### PROFIBUS FC Trailing Cable

Highly flexible bus cable (2-core), sold by the meter, unassembled PROFIBUS FC Trailing Cable, PROFIBUS trailing cable, max.

Acceleration 4 m/QS min. 3 million bending cycles min. Bending radius approx. 120 mm 2-wire shielded Sold by the meter Delivery length max. 1000 m Minimum order 20 m



Suitability for use

Continuous motion control in a cable carrier

Cable designation

02YY (ST) C11Y 1x2x0,65/2,56-150 LI KF 40 FR petrol

### Electrical data

Damping ratio per length

• at 9.6 kHz / maximum	0.003 dB/m
• at 38.4 kHz / maximum	0.004 dB/m
• at 4 MHz / maximum	0.025 dB/m
• at 16 MHz / maximum	0.049 dB/m

Impedance

• Rated value	150 Ω
• at 9.6 kHz	270 Ω
• at 38.4 kHz	185 Ω
• at 3 MHz ... 20 MHz	150 Ω

Relative symmetrical tolerance

• of the characteristic impedance at 9.6 kHz	10 %
• of the characteristic impedance at 38.4 kHz	10 %

<ul style="list-style-type: none"> <li>of the characteristic impedance at 3 MHz ... 20 MHz</li> </ul>	10 %
Loop resistance per length / maximum	133 mΩ/m
Shield resistance per length / maximum	14 Ω/km
Capacity per length / at 1 kHz	28 pF/m
Operating voltage <ul style="list-style-type: none"> <li>RMS value</li> </ul>	80 V

### Mechanical data

Number of electrical cores	2
Design of the shield	Overlapped aluminum-clad foil, sheathed in a braided screen of tin-plated copper wires
Type of electrical connection / FastConnect	Yes
Outer diameter <ul style="list-style-type: none"> <li>of inner conductor</li> <li>of the wire insulation</li> <li>of the inner sheath of the cable</li> <li>of cable sheath</li> </ul>	0.67 mm 2.56 mm 5.4 mm 8 mm
Symmetrical tolerance of the outer diameter / of cable sheath	0.4 mm
Material <ul style="list-style-type: none"> <li>of the wire insulation</li> <li>of the inner sheath of the cable</li> <li>of cable sheath</li> </ul>	polyethylene (PE) PVC PUR (TPE-U)
Color <ul style="list-style-type: none"> <li>of the insulation of data wires</li> <li>of cable sheath</li> </ul>	red/green petrol
Bending radius <ul style="list-style-type: none"> <li>with single bend / minimum permissible</li> <li>with continuous bending</li> </ul>	40 mm 120 mm
Number of bending cycles	3000000; Drag chain suitable for 3 million bending cycles at a bending radius of 120 mm (15x D), a speed of 4 m/s and an acceleration of 4 m/s <sup>2</sup>
Tensile load / maximum	100 N
Weight per length	77 kg/km

### Ambient conditions

Ambient temperature <ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> <li>during transport</li> <li>during installation</li> <li>Note</li> </ul>	-40 ... +60 °C -40 ... +60 °C -40 ... +60 °C -40 ... +60 °C Electrical properties measured at 20 °C, tests according to DIN 47250 part 4 respectively DIN VDE 0472
---	--

Ambient condition / for operation	Limited segment length (see manual for PROFIBUS networks)
Burning behavior	flame resistant according to IEC 60332-1-2
Class of burning behaviour / according to EN 13501-6	Eca
Chemical resistance <ul style="list-style-type: none"> <li>• to mineral oil</li> <li>• to grease</li> <li>• to water</li> </ul>	oil resistant according to IEC 60811-2-1 (7x24h/90°C) resistant conditional resistance
Radiological resistance / to UV radiation	resistant

#### Product features, product functions, product components / general

Product feature <ul style="list-style-type: none"> <li>• halogen-free</li> <li>• silicon-free</li> </ul>	No Yes
--	-----------

#### Standards, specifications, approvals

UL/ETL listing / 300 V Rating	Yes; c(UL)us / CMX
UL/ETL style / 600 V Rating	Yes; cRU AWM I A/B 80°C 600V FT2
Certificate of suitability <ul style="list-style-type: none"> <li>• CE marking</li> <li>• RoHS conformity</li> </ul>	Yes Yes
Marine classification association <ul style="list-style-type: none"> <li>• American Bureau of Shipping Europe Ltd. (ABS)</li> <li>• Bureau Veritas (BV)</li> <li>• Det Norske Veritas (DNV)</li> <li>• Germanische Lloyd (GL)</li> <li>• Lloyds Register of Shipping (LRS)</li> <li>• Nippon Kaiji Kyokai (NK)</li> <li>• Polski Rejestr Statkow (PRS)</li> </ul>	No No No No No No No

#### Further information / Internet-Links

Internet-Link <ul style="list-style-type: none"> <li>• to website: Selector SIMATIC NET SELECTION TOOL</li> <li>• to website: Industrial communication</li> <li>• to website: Industry Mall</li> <li>• to website: Information and Download Center</li> <li>• to website: Image database</li> <li>• to website: CAx Download Manager</li> <li>• to website: Industry Online Support</li> </ul>	<a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a> <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a> <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a> <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a> <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
--	---

**last modified:**

10/26/2019